

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 25.04.2018

Revision: 29.03.2018

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

For professional use only

- **1.1 Product identifier** For professional use only
- **Trade name:** B72 Acrylic Adhesive
- **Article number:** 8627
- **1.2 Relevant identified uses of the substance or mixture and uses advised against** Surface Coating
- **Application of the substance / the mixture**  
Surface Coating  
Surface Coating
- **1.3 Details of the supplier of the safety data sheet**
- **Supplier:**  
HMG PAINTS LIMITED  
RIVERSIDE WORKS, COLLYHURST ROAD,  
MANCHESTER. M40 7RU  
UNITED KINGDOM  
TEL: +44 (0)161 205 7631  
EMAIL: sales@hmgpaint.com
- **Further information obtainable from:** sales@hmgpaint.com
- **1.4 Emergency telephone number:** +44 (0)161 205 7631 (Business hours)

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**  
Flam. Liq. 2 H225 Highly flammable liquid and vapour.  
Eye Irrit. 2 H319 Causes serious eye irritation.  
STOT SE 3 H336 May cause drowsiness or dizziness.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** Danger
- **Hazard-determining components of labelling:**  
propan-2-one
- **Hazard statements**  
H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.
- **Precautionary statements**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 25.04.2018

Revision: 29.03.2018

**Trade name: B72 Acrylic Adhesive**

(Contd. of page 1)

- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P303+P361+P353 **IF ON SKIN (or hair):** Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Additional information:**

- EUH066 Repeated exposure may cause skin dryness or cracking.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**

- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2	propan-2-one ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	50-100%
CAS: 9004-70-0	Nitrocellulose (12.3% N) ⚠ Expl. 1.1, H201	2.5-10%
CAS: 67-63-0 EINECS: 200-661-7	propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	≤ 2.5%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.

- **After skin contact:**

Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing.

- **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:**

Do not induce vomiting; call for medical help immediately and show safety datasheet or label.

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **4.3 Indication of any immediate medical attention and special treatment needed** Treat symptomatically.

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**

- **Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

- **5.3 Advice for firefighters**

- **Protective equipment:** Put on breathing apparatus

GB

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 25.04.2018

Revision: 29.03.2018

Trade name: B72 Acrylic Adhesive

(Contd. of page 2)

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Prevent seepage into sewage system, workpits and cellars.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Ensure adequate ventilation.
- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Keep receptacles tightly sealed.
- **Information about fire - and explosion protection:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed and in a well-ventilated place.  
Keep away from heat.  
Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

#### 67-64-1 propan-2-one

WEL Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm  
Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

#### 67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 999 mg/m<sup>3</sup>, 400 ppm

- **DNELs**

#### 67-64-1 propan-2-one

Oral	DNEL	62 mg/day (Con)
Dermal	DNEL	62 mg/day (Con)
		186 mg/day (Ind)
Inhalative	DNEL	200 mg/m <sup>3</sup> (Con)
		1,210 mg/m <sup>3</sup> (Ind)

(Contd. on page 4)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 25.04.2018

Revision: 29.03.2018

**Trade name: B72 Acrylic Adhesive**

(Contd. of page 3)

**67-63-0 propan-2-ol**

Oral	DNEL	26 mg/day (Con)
Dermal	DNEL	319 mg/day (Con)
		888 mg/day (Ind)
Inhalative	DNEL	89 mg/m <sup>3</sup> (Con)
		500 mg/m <sup>3</sup> (Ind)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Particulate cartridge filter type when LEV cannot be supplied

· **Protection of hands:**

When skin exposure may occur, advice should be sought from the glove supplier on appropriate types and usage times for this product.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Colour: Clear

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 56°C

· **Flash point:** -17°C

· **Flammability (solid, gas):** Not applicable.

· **Ignition temperature:** 540°C

· **Decomposition temperature:** Not determined.

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 25.04.2018

Revision: 29.03.2018

Trade name: B72 Acrylic Adhesive

(Contd. of page 4)

· <b>Auto-ignition temperature:</b>	Product is not selfigniting.
· <b>Explosive properties:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b>	
<b>Lower:</b>	2.6 Vol %
<b>Upper:</b>	13.0 Vol %
· <b>Vapour pressure at 20°C:</b>	233 hPa
· <b>Density at 20°C:</b>	0.924 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not determined.
· <b>Solubility in / Miscibility with water:</b>	NOT MISCIBLE
· <b>Partition coefficient: n-octanol/water:</b>	Not determined.
· <b>Viscosity:</b>	
<b>Dynamic:</b>	Not determined.
<b>Kinematic at 20°C:</b>	48 s (DIN 53211/4)
· <b>Solvent content:</b>	
<b>Organic solvents:</b>	56.9 %
<b>Solids content:</b>	45.7 %
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**  
No dangerous decomposition products when stored and handled correctly

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

<b>67-64-1 propan-2-one</b>		
Oral	LD50	5,800 mg/kg (Rat)
Dermal	LD50	15,800 mg/kg (Rat)
Inhalative	LC50/4 h	76 mg/l (Rat)
<b>9004-70-0 Nitrocellulose (12.3% N)</b>		
Oral	LD50	>5,000 mg/kg (Rat)
<b>67-63-0 propan-2-ol</b>		
Oral	LD50	>5,000 mg/kg (Rat)
Dermal	LD50	>5,000 mg/kg (Rab)
Inhalative	LC50/4 h	>25 mg/l (Rat)

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 25.04.2018

Revision: 29.03.2018

**Trade name: B72 Acrylic Adhesive**

(Contd. of page 5)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- |                                       |  |
|---------------------------------------|--|
| · <b>14.1 UN-Number</b>               |  |
| · <b>ADR, IMDG, IATA</b>              | UN1133   |
| · <b>14.2 UN proper shipping name</b> |  |
| · <b>ADR</b>                          | 1133 ADHESIVES (vapour pressure at 50°C not more than 110 kPa) |
| · <b>IMDG, IATA</b>                   | ADHESIVES  |

(Contd. on page 7)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 25.04.2018

Revision: 29.03.2018

Trade name: B72 Acrylic Adhesive

(Contd. of page 6)

## · 14.3 Transport hazard class(es)

· ADR, IMDG, IATA



· Class 3 Flammable liquids.  
· Label 3

## · 14.4 Packing group

· ADR, IMDG, IATA II

## · 14.5 Environmental hazards:

· Marine pollutant: No

## · 14.6 Special precautions for user

Warning: Flammable liquids.  
· Danger code (Kemler): 33  
· EMS Number: F-E,S-E  
· Stowage Category B

## · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

## · Transport/Additional information:

## · ADR

· Limited quantities (LQ) 5L  
· Excepted quantities (EQ) Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml  
· Transport category 2  
· Tunnel restriction code D/E

## · IMDG

· Limited quantities (LQ) 5L  
· Excepted quantities (EQ) Code: E2  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 500 ml

## · UN "Model Regulation":

UN 1133 ADHESIVES (VAPOUR PRESSURE AT 50°C NOT MORE THAN 110 KPA), 3, II

### SECTION 15: Regulatory information

## · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:

· Technical instructions (air):

Class	Share in %
NK	56.9

· Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 25.04.2018

Revision: 29.03.2018

Trade name: **B72 Acrylic Adhesive**

(Contd. of page 7)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Relevant phrases**

H201 Explosive; mass explosion hazard.  
H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

· **Department issuing SDS:** Product safety department: LABORATORY

· **Contact:** Health & Safety Officer

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Expl. 1.1: Explosives – Division 1.1

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

GB